

LMWB04, 06

CATALOGUE 2024-25

**Digital Water Bath****LMWB04, 06****SALIENT FEATURES**

- It adopts new design structure, which could avoid the leakage of steam.
- There are pointer type temperature controller and intellectual type temperature controller for selecting. The intellectual temperature controller has high lightness digital display and key operating button, which is easy to operate. It has high precision on controlling the temperature.

Thermostatic Water Baths Uses Evaporating, drying, concentrating and thermostatically heating. Widely adopted in medical and research units factories, universities, chemical dyeing and petroleum



E - Catalogue

HSN Code : 84192090

SPECIFICATIONS	Model	LMWB04	LMWB06
	Column	2 rows 4 holes	2 rows 6 holes
	Make	LABMAN	
	Temp. range	Rt+5~100°C	
	Temp. Resolution Ratio	0.1°C	
	Temp. Accuracy	±0.5°C	
	Temp. Uniformity	±1°C	
	Water sink	Stainless steel, surface electrolysis treatment	
	Outer shell	Cold rolled steel plate, surface electrostatic powder spray	
	Heater	Stainless steel U type heating tube	
	Temp. control mode	PID	
	Timer	0∞999 min (with timing function)	
	Timing function	Fixed temperature operation, timing function, auto stop.	
	Program	Optional: multi-section program control	
	Additional function	Deviation correction, menu key lock, power failure back-up, power-off parameter memory, PID adjustable	
	Sensor	Thermal resistor	
	Safety device	Over-temperature alarm, short-circuit protection	
	Power rating	800W	1200W
	Inner Chamber size(WxLxH)mm	305x305x135	470x305x130
	Packing size (WxLxH) (mm)	405x405x250	565x405x250
Internal volume (approx.)	12L	18L	
Cover aperture	∅120mm		
Cover Rings per hole	5		
Power Supply	Adaptor, Using AC 220V,50/60Hz		
Weight	6.5kg	8kg	

★ Specifications are subject to change without notice.

STANDARD ACCESSORIES : Main Instrument, ABS Beaker Holder, Aluminium Heater Cover, Test Certificate