

WinnerOne

Reliable Acrylic Wall Putty



HomeCoat WinnerOne Reliable Acrylic Wall Putty is a ready-to-use water-based paste putty. It is formulated specially as a premium decorative interior coating using proprietary acrylic binder & superfine fillers. Putty is meant for filling out cracks and dents, and smoothen the plastered wall or similar interior surfaces. It provides strong, durable foundation and brings out the best performance from the finish paints, both in looks and in durability.



WATER BASED



Key Features



High penetration power & retains a strong grip on the wall surface



Smooth finish



Quick Drying



Acid & Alkali Resistance



Superior adhesion on normal & moist surfaces



Improved durability & life



Brilliant white tone



Technical Data

Property	Data
Application Method	Putty knife
Covering**	15-20 sqft per kg (double coat)
Finish	Smooth
PH	8 to 9
Thinning	Ready to use, or 3-5% depending on the application.
Drying Time	Dry to touch 30 minutes
Shelf Life	1 year in original packaging away from direct sunlight and excessive heat
Recommended DFT	0.5 – 1.0 mm
Recommended Method	Interior Primer : 1 Coat Acrylic Putty : 2 Coats Interior Primer : 1 Coat Interior Paint : 2 Coats

**Actual coverage may vary on factors such as substrate porosity, method of application etc. It is advisable and strongly recommended to check the covering on respective surface before use.



Pack Sizes and Shade Range

Pack Size Availability :- 2 Kg, 5 Kg, 10 Kg, 20 Kg

Shade :- White



Substrate Suitability

Home Coat's WinnerOne Acrylic Putty is compatible to the following substrates



Asbestos sheets



Concrete



Plaster



Surface preparation

- Ensure that the surface to be painted is free from any loose paint, dust or grease.
- Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- On fungus affected areas apply a coat of 'Bio Wash' solution. Allow it to dry for 4-6 hours.



Direction for use

- Apply WinnerOne Reliable Acrylic Putty by Putty knife or spray. Moisten the wall and apply one coat of putty with the help of a putty knife.
- Draw the blade from bottom to top while applying the putty. Make the surface smooth using water paper no. 400 or a soft wet cloth.
- Cut the surface and apply another coat after 3-4 hours.
- Clean the surface to give a final thickness of 1.5 mm, using emery paper no. 400.
- Clean the cut surface with soft wet cloth or wet sponge and allow 3 days before applying the top coat.



Precautions

- Prior to use, read and follow product specification, MSDS and label information.
- Do not over thin
- Do not apply WinnerOne Acrylic Putty in the form of single coat or thick layer application.
- Avoid contact with eyes and skin.
- Use safety equipment like rubber or polythene gloves, safety goggles / glasses and face masks



HomeCoat OPC Pvt. Ltd.

📍 **Factory:** A10, Balaji Industrial Estate, Tondre, Talaja MIDC, Panvel 410206

📍 **Reg. Office :** 101, PrabhuKripa, Plt no 10&12, Rd no 13, Sect 19, New Panvel, Raigad 410206

☎ **8260013001** ✉ connect@homecoat.in 🌐 www.homecoat.in