



# AUTO TAKE 15W40

## Diesel Auto Engine oil

### PRODUCT DESCRIPTION

LUBXTAR AUTO TAKE 15w40 is high performance heavy duty diesel engine oil specifically developed for low emission vehicles to extend engine life in the most severe duty on and off-highway application.

### APPLICATIONS

Diesel engine of all leading engine manufactures where such performance level oil is recommended.  
On –highway application including light duty Auto.

### FEATURES & BENEFITS

- Exceptional oxidation stability reduces engine deposits, sludge build-up and oil thickening.
- Outstanding soot handling capability minimizes soot related viscosity increase and wear.
- High shear stability maintains viscosity at elevated temperatures leading to improved wear protection and reduced oil consumption.
- Superior protection against corrosive wear extends life of engine components.

### SPECIFICATION & TYPICAL PROPERTIES

SAE Viscosity Grade	15w40	
Mets the following specifications		
API CF -4/SJ	x	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity @100°C,cst	D 445	13.5 -15.5
viscosity Index, Min	D 2270	125
Flash Point, °c,Min	D 92	210
Pour Point, °c,Max	D 97	-24
TBN ,mg KOH/g	D 2896	8.0 to 11.0

Manufactured by :

**LUBXTAR INDUSTRIES PRIVATE LIMITED**

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

