



# BREAK FLUID DOT-III

Brake Fluid

## PRODUCT DESCRIPTION

LUBXTAR Brake fluid is a premium quality heavy-duty hydraulic brake fluid processed from carefully selected ingredients and blended with a balance Combination of antioxidant, metal deactivator and corrosion inhibitor.

## APPLICATIONS

Brake and clutch fluid is recommended for use in disc and drum hydraulic brake system of all passenger Cars, Trucks, Tractors, Buses and Heavy Duty Vehicles.

## FEATURES & BENEFITS

- Ensure extra safe due to high 'dry' and 'wet' boiling point.
- Ensure excellent protection against corrosion to iron, non-ferrous metal.
- Ensures compatibility with rubber seals and cups
- Ensures longer service life, due to excellent oxidation stability

## SPECIFICATION & TYPICAL PROPERTIES

Grade		BREAK FLUID DOT -III
Mets the following specifications		
IS: 8654/1986, DOT -3 and exceeds S AE J -1703 specifications		x
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity @100°C,cst	D 445	1.5
Equilibrium Reflux Boiling Point (ERBP) °C	D 1120	210
Wet ERBP °C		140
PH value	D 1287	7.0- 11.5
Compatibility		pass
Colour	D 1500	Red

Manufactured by :

**LUBXTAR INDUSTRIES PRIVATE LIMITED**

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

