



CNG AUTO 20W50

Light-duty Auto Engine oil

PRODUCT DESCRIPTION

LUBXTAR CNG AUTO 20w50 is formulated from selected additives to provide superior detergency and dispersancy, oxidation and nitration resistance and protection against engine wear and corrosion.

APPLICATIONS

Light –duty Vehicles on CNG, LPG or propane and operating under moderate service condition

Other spark ignited gas engines where API SL/CF quality oils are specified

FEATURES & BENEFITS

- Effective detergency and dispersancy keeps engines cleaner
- Provides protection against corrosion
- Provides superior protection against engine wear.
- Controls combustion chamber carbon and ash deposits.

SPECIFICATION & TYPICAL PROPERTIES

SAE Viscosity Grade	20W50	
Mets the following specifications		
API SL/CF	X	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity @100°C,cst	D 445	17.5 -19.5
viscosity Index, Min	D 2270	120
Flash Point,°c,Min	D 92	235
Pour Point,°c,Max	D 97	-24
Sulphated Ash,%wt,Max	D 874	0.8
TBN ,mg KOH/g	D 2896	5.0-7.0

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

