



GEAR MAX EP-140

Extreme Pressure Gear oil

PRODUCT DESCRIPTION

LUBXTAR GEAR MAX EP-140 is premium quality extreme pressure gear lubricating oil, blended from solvent refined base oils having high viscosity index with extremely good oxidation stability. These oils are blended with selected extreme pressure additives, to provide antifoam, anti-war and antirust properties.

APPLICATIONS

Lubrication of axles and mechanical transmission systems of cars, buses, trucks and tractors which require moderate duty GL-4 type of gear oils

FEATURES & BENEFITS

- Anti-foaming with enhanced ability to form lubricating film
- High oxidation stability and increased drain period interval.
- Free from suspended matter, grit, water or any other impurities

SPECIFICATION & TYPICAL PROPERTIES

SAE Viscosity Grade		EP-140
Mets the following specifications		
API GL-4		x
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity @100°C,cst	D 445	28-34
viscosity Index,Min	D 2270	90
Flash Point,°c,Min	D 92	180
Pour Point,°c,Max	D 97	-9

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

