



BREAK FLUID DOT-IV

Brake Fluid

PRODUCT DESCRIPTION

LUBXTAR Brake fluid is a premium quality heavy-duty hydraulic brake fluid processed from carefully selected ingredients and blended with a balance Combination of antioxidant, metal deactivator and corrosion inhibitor.

APPLICATIONS

Brake and clutch fluid is recommended for use in disc and drum hydraulic brake system of all passenger Cars, Trucks, Tractors, Buses and Heavy Duty Vehicles.

FEATURES & BENEFITS

- Ensure extra safe due to high 'dry' and 'wet' boiling point.
- Ensure excellent protection against corrosion to iron, non-ferrous metal.
- Ensures compatibility with rubber seals and cups
- Ensures longer service life, due to excellent oxidation stability

SPECIFICATION & TYPICAL PROPERTIES

Grade	BREAK FLUID DOT -IV	
Mets the following specifications		
IS: 8654/1986, DOT -IV and exceeds S AE J -1703 specifications		
		x
Typical Properties		
Test Parameters	ASTM Method	Typical values
Viscosity @100°C,cst	D 445	1.5
Equilibrium Reflux Boiling Point (ERBP) °C	D 1120	230
Wet ERBP °C		155
PH value	D 1287	7.0- 11.5
Compatibility		Pass
Colour	D 1500	WATER WHITE

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

