



COMPRESSOR 220

Compressor oil

PRODUCT DESCRIPTION

LUBXTAR Compressor is formulated from a high grade base stock with a narrow distillation range, containing specially selected additives, which enhance lubricated, anti-wear properties, and protect compressor parts against rust. It is designed to lubricate both cylinders and crankcases. It minimizes carbon and sludge deposits, thereby extending time between service intervals for cleaning valves, ports and intercoolers.

APPLICATIONS

Recommended for use Single & Multi-stage reciprocating compressors.

FEATURES & BENEFITS

- Longer intervals between cleaning of valves, heat exchangers ports and ensure lower maintenance cost.
- Less carbon and deposit formation reduces fire and explosion hazards.
- Single oil, lubricates cylinders and crankcase.
- Suitable for both large and small compressors.

SPECIFICATION & TYPICAL PROPERTIES

ISO Viscosity Grade		220
Mets the following specifications		
DIN 51506 VDL		x
Typical Properties		
Test Parameters	ASTM Method	Typical values
Specific Gravity @ 15 °C	D 4052	0.888
Viscosity @100°C,cst	D 445	220.0
Viscosity @100°C,cst	D 445	26.5
viscosity Index	D 2270	96
Flash Point(COC),°c	D 92	260
Pour Point , °C	D 97	-6
Colour	D 1500	2.5
Rust Test		pass

Manufactured by :

LUBXTAR INDUSTRIES PRIVATE LIMITED

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

