



## HYDRAULIC-15

Low Viscous Circulation oil

### PRODUCT DESCRIPTION

LUBXTAR HYDRAULIC-15 Oil is blended from high quality, chemically-stable solvent refined base oils and incorporated with balanced additive system which include anti wear and oxidation inhibitors.

### APPLICATIONS

Recommended for use most types of hydraulic systems, moderately-loaded gears and bearing lubricated by circulation and bath and ring oiling

### FEATURES & BENEFITS

- Excellent anti-wear performance.
- Provide rust and corrosion protection.
- Hydrolytic stability
- Low friction
- Excellent water separation, air release and antifoam properties

### SPECIFICATION & TYPICAL PROPERTIES

Grade	15	
Mets the following specifications		
DIN 51524 (Part II), Denison HF -O, HF -2	x	
Typical Properties		
Test Parameters	ASTM Method	Typical values
Specific Gravity @ 15 °C	D 4052	0.832
Viscosity @100°C,cst,Min	D 445	15.2
Viscosity @100°C,cst,Min	D 445	3.85
viscosity Index, Min	D 2270	141
Flash Point(COC), °c, Min	D 92	185
Pour Point , °C, Max	D 97	-42
Colour	D 1500	0.5
Neutralization No. mg KOH/g	D 974	0.38

Manufactured by :

**LUBXTAR INDUSTRIES PRIVATE LIMITED**

Survey No.92,Gharat wadi,Near Khan Compound, Pelhar,

Vasai East, Mumbai Maharashtra -401208.

Customer Care No.: +91 8780097367

Email : lubxtarindustries@gmail.com

web.www.lubxtar.com

