

**CERTIFICATE OF
FURNACE OIL**

REPORT NO: - LX-LAB-123704-24

Client: -		
Sample Description: FURNACE OIL		
Sample Delivered By:	Sample Drawn By : N/A	
Condition of Sample Received:	1 x 500 ml plastic bottle,	
Date Received: 01-06-2024	Date Tested: 03-06-2024	Date Reported: 03-06-2024

TEST RESULTS

Test	Method	Unit	Result
Colour	ASTM D 1500	VISUAL	Dark black
Flash Point	ASTM D 93	°C	85
Density @ 15 °C	ASTM D 1298	Kg/L	0.9685
Kinematic Viscosity 40 °C	ASTM D 445	cSt	134.08
Calorific Value/kg	ASTM D 240	Cal/g	10120
Pour point	ASTM D 97	°C	15
Condensation carbon Residue	ASTM D 189	%	10.28
Sulphur wt%	ASTM D 1298	%	2.26
Moisture wt%	ASTM D 4377	%	0.60
Sediment wt%	ASTM D 4898	%	0.27
Ash Content wt%	ASTM D 482	°C	0.02

Checked and Approved By:

LUBXTAR INDUSTRIES PRIVATE LIMITED

(RAJESH YADAV)
Authorized Signatory