

VERTICAL ELECTRIC SUMBMERSIBLE JET AERATOR PUMP

→ APPLICATION:

Waste Water Tretment aeration and agitation.

Mixing and Stirring application for uniform MLSS,

Easy reduction in BOD level from waste water.

SPECIFICATION

High Oxygen Transfer Rate.

Range : 1.1 KW/1.5 HP to 5.5KW/7.5 HP

Speed:2880 RPM (2 POLE)

Degree of Protection: As Per IP: 68

Insulation class: F

Version: AC 50Hz, Single Phase upto 2hp & 3 Phase upto 7.5 hp

Motor: Copper Winding

Motor Type: Dry/Oil Filled

Direction Of Rotation: Clockwise viewed from driving end

Duty:S1

Pump Moc: CI/SS304/SS316

Sealing: Double Mechnical Seal With Customized Faces



T.		TA	THE RESERVE TO SERVE THE PARTY OF THE PARTY			OUSTRIES OR JET AERATO	OR PUMP		
PUMP MODEL	Motor Rating		DEL		RPM	RATED AIR	AERATION TANK		
	ĸw	HP	MM	Phase		M3/HR	L (M)	W (M)	H (M)
KVJA 112AE	0.75	1	50	1	2850	11	3	3	3
KVJA 132AE	0.75	1	50	3	2850	11	3	3	3
KVJA 1512AE	1.1	1.5	50	1	2850	22	3	3	3
KVJA1532AE	1.1	1.5	50	3	2850	22	3	3	3
KVJA 212AE	1.5	2	50	1	2850	25	4	3.5	3
KVJA 232AE	1.5	2	50	3	2850	25	4	3.5	3
KVJA 333AE	2.2	3	80	3	2850	42	5	4.5	4
KVJA 534AE	3.7	5	100	3	2850	72	6	5	5
KVJA 7534AE	5.5	7.5	100	3	2850	100	7	6.5	6

KDS PUMPS INDUSTRIES.