TX 20

SINGLE INPUT DUAL OUTPUT SIGNAL ISOLATOR



Features

- Single Input, Dual Output
- Signal Conversion with Isolation
- Dedicated Input
- Accuracy better than 0.25% F. S.
- 24 V DC Supply
- Compact Size & Easy Maintenance
- Din Rail Mount
- Reliable & Cost Effective System



Description

Electronet series TX-20 are Signal Isolators with single input, dual output specially used for various industrial applications. It can interface inputs like Current, Voltage & provide isolated output in terms of Current or Voltage. The compact design saves inner space required in panel to mount the instrument.

Technical Specifications

| Performance Characteristics | | | |
|-----------------------------|---|--|--|
| No. of Input | 01 No. | | |
| No. of Output | 02 Nos. | | |
| Type of Input | Dedicated | | |
| | 1) Current (4-20 mA) | | |
| | 2) Voltage (0-5 V / 1-5 V) | | |
| Type of Output | Dedicated | | |
| | 1) Isolated mA (4-20 mA) | | |
| | 2) Isolated Volt (0-5 V DC) | | |
| Accuracy | +/- 0.25% F. S. | | |
| Isolation | 1.5 KV between Input, Output & Power Supply | | |
| Power Supply | 24 V DC | | |
| Power Consumption | < 4 VA | | |
| Response Time | < 50 mSec | | |
| Temperature Coefficient | +/- 0.01% per °C | | |
| Enclosure | ABS Plastic | | |
| Dimensions | 75 mm (H) x 22 mm (W) x 110 mm (D) | | |
| Mounting | Din Rail Type | | |
| Weight | 250 gms | | |
| Operating Conditions | Temperature -20 to 55 °C / Humidity 5 to 95% non condensing | | |

www.eeplindia.com EEPL-S063B-270925 01 of 02



Ordering Information

Sample Order Code: TX 20-A1-B1-C1

| Parameter | | Code | Value |
|-----------|----------|---------|-------------------|
| A Input | | A1 | 4 to 20mA |
| | | A2 | 0 to 5V / 1 to 5V |
| | А3 | Current | |
| | | A4 | Voltage |
| | | AY | Other |
| | Output 1 | B1 | 4 to 20mA |
| В | Output 1 | B2 | 0 to 5V |
| | Output 2 | C1 | 4 to 20mA |
| С | | C2 | 0 to 5V |

Note:

- Due to our continuous product revisions, design specification and model numbers are subject to change without notice.
- Accuracy defined at Lab Conditions.
- For other requirement please consult factory.
- This product is meant for laboratory/Process application only and not for custody transfer application.

ELECTRONET EQUIPMENTS PVT. LTD.

Registered Office:

Factory Address:

Plot No. 84, 85, 86, Tiny Industrial Estate, Kondhwa Budruk, Pune-411 048, Maharashtra, India.

Plot No. 8, (SEZ) Phase 1, Kesurdi MIDC, Khandala, Dist.- Satara Pin: 412 801, Maharashtra, India.



+91-20-26931476 ho@electronet.co.in enquiries@electronet.co.in

