

Frequently Asked Questions

Questions		Reasons	Precautions	Countermeasure
For Paint	Nozzle blocked during spraying	1.Paint sprayed without been shaken well. 2.Glass beads crushed due to fiercely, shaking, blocking the nozzle. 3.Paint resides on the nozzle after each painting. When dried, paint residual will block the nozzle. 4.Paints are stored upside down or flatwise. Subsided pigment blocked the nozzle.	1.Stirring paints evenly for about 2 minutes before spraying. 2.Shaking properly by holding the can with a 45 angle horizontally without shaking too strongly. 3.Clean the paint residual by spraying for 3 seconds with the can upside down. 4.Do not store paints upside down.	Take off the nozzle, stir the paint evenly and spraying for 3 seconds with the can upside down and replace the nozzle with a new one.
	Insufficient Pressure	1.Too much spraying with upside down. 2.Spraying out more air with less paint by inclining over 45 degrees. 3.Paint expired , external environments too.	1.Do not take too much upside - down spray. 2.Do not spray with can inclining over 45 degree. Do not use expired paint.	Try to spray all the paint in one time when found pressure insufficient.
	Surface of paint looks white, and weak in covering	1.Unevenly stirring before spray. 2.Spraying out more air with less paint by inclining over 45 degrees. 3.External environment is too cold. 4.High humidity with little airflow, too thick spray for one time (pearl paint).	1.Spray properly with thin spray for more times. Do not spray upside down or over inclined. 2.Try not to spray in wet or cold days. Add retarders if you have to spray in wet days.	Choose a better environment to spray or bake with infrared lamps (<60deg.)For a little white surface try with a furniture polisher. For serious white surface, erase the paint with P800 abrasive paper and spray.
After Painting	Sagging or paint drops	1.Not enough spray distance between nozzle and targets. 2.Too slow spray 3.Poor air ventilation 4.Short dry time between two sprays, the former paint layer's wet.	1.Spray distance shall be 15-25cm 2.Spray speed 30-60cm/s. 3.Keep good air flow. 4.Keep dry time between 5-15 min. subject to different environment	For slight sagging, let the paint dried completely (16 hours with room temperature), try to erase with P1500 abrasive paper and polish with wax. For serious sagging erase the paint.
	Dust or particle	1.The target surface is not clean 2.Dust pollution from spray environment, Pollution from other sources, the operators etc.	1.Keep the target surface clean. 2.Make sure the environment is clean, clean all possible pollution sources.	For slight dust pollution, try to erase with P1200 abrasive paper and polish with wax. For heavy dust, erase the paint.
	Paint crackle or corrugation	1.Two layer of paints are different, chemical reaction happens between solvents. 2.A new layer of paint is sprayed before the old paint layer get dry. 3.Too thick spray on the surface	1.Small size test to make sure two paints are workable 2.Spray properly, erase the aging base paint before spray a new layer.	Erase the base paint completely and spray again.
	Paint peeling off or scaling	1.Greasy dirt, water or dust left on the surface of paint target. 2.Surface of paint target is too glossy or not polished.	1.Keep the target surface clean 2.Roughen the target surface with abrasive paper and spray anti-rust paint.	Erase the unstable paint with P800 abrasive paper and spray again.
	Paint get rusted	1.Incomplete rust clean on the target surface. 2.Fail to give timely treatment on the paint flaw, pinholes, water, bubbles etc. No anti-rust treatment is given to the target.	1.Keep the target surface clean and spray anti-rust paint. 2.Make sure the paint layer is thick enough and complete.	Remove the paint with paint remover, roughen with P800 abrasive paper and spray again.



Be Bold



 www.glutape.com

 9834161900 / 8779837559





Normal Spray Paint

4 Matt Black	6 Orange Red	8 Mars Red	14 JIALING Red	15 Sky Blue	22 Medium Grey	23 Scarlet
25 Medium Yellow	27 Leaf Green	28 Deep Blue	29 Mission Brown	33 Cream Yellow	36 Silver	37 Fresh Green
39 Black	40 White	41 Canary Yellow	68 Orange Yellow	83 Violet	101 Jade Green	131 Suzuki Red
137 Deep Red	190 Lacquer	191 Lacquer Matt	219 Shifeng Blue	226 Orange	228 Bright Red	238 Ford Blue
242 River Blue	243 Rose	301 Grey	304 Deep Grey	331 Xiali Red	332 Santana Red	352 Jiefang 142 Blue
1210 Anti-Rust Brown						



Metallic Spray Paint

343 Flash Violet Blue	67+36 Honda Clarity Red	35 Gold	C1 Bright Chrome	319 Bright Gold	1300 Silver

Chrome Effect Spray Paint

Gold Spray Paint

Heat Resistant Spray Paint

1200 Black



Fluorescent Spray Paint

1001 Fluorescent Red	1002 Fluorescent Pink	1003 Fluorescent Green	1004 Fluorescent Blue	1005 Fluorescent Yellow
1006 Fluorescent Orange	1007 Fluorescent White	1012 Fluorescent Magenta	1013 Fluorescent Violet	



* Shade variation of 10% - 15% may occur against actual shade.

Normal Spray Paint



Normal Spray Paint

This product is Aerosol Spray Paint made of advanced resin, pigments and auxiliaries. With characteristics of rapid drying, even delicate paint film, powerful good atomization type and high spray rate. It is suitable for spraying and repairing surfaces of metal, wood, glass, leather and various substrates.



Fluorescent Spray Paint



Fluorescent Spray Paint

This product is Aerosol Spray Paint with excellent fluorescent effect. The product has a superb drying time, and it is ideally used for metals, surface treated wood, glass, ABS plastic and many other substrates.



Gold Spray Paint



Gold Spray Paint

This Aerosol Spray Paint is made of metallic pigment and advanced resin. The product brings gold-plated effect when applied on the substrate. It has the properties of quick drying, strong metal mirror effect, atomizing effect and even delicate coating. The product performance with the surfaces like metal, treated wood, glass, ABS Plastic, along various substrates.



Heat Resistant Spray Paint

This Aerosol Spray Paint is made of organic silicon resin, withstanding high temperature up to 500°C. The product features easy operation, good sprayability and high delivery rate. It is suitable for all types of substrate with high temperature like chimney, exhaust pipe and etc. Bring excellent protection against rust and UV radiation.



Metallic Spray Paint



Chrome Effect Spray Paint



Heat Resistant Spray Paint