

Prime Ratings Range	
	GGP35EKL
	50Hz
kVA	35



The GGP-Escorts Kubota Advantage

- One-stop solution for the generating system and accessories
- Manufactured in India with global expertise
- Compact design with ease of maintenance
- Max winding provides excellent motor starting capability
- Flexible & creative customized solutions to meet customer needs
- Fast response time
- Two-years or 5000 hours as per standard warranty terms from date of initial startup

Special Features

Natural aspirated industrial diesel engine with superior efficiency and operating economy

- Integral vibration isolation eliminates the need for under-unit vibration spring isolators
- Advanced Digital Controller (ADC) with 3 auto crank cycles and inbuilt AMF logic
- Alternator features:
 - Alternator meets Indian and international standards
 - Self-ventilated and drip proof of IP23 construction
 - Superior voltage waveform by 2/3 pitch wound stator
 - Sustained short circuit current of up to 300% of the rated current
- Silencer located inside canopy

Standard Features

- Engine mounted battery charging alternator
- Single - bearing alternator with insulation Class H
- Unit mounted radiator with 50°C ambient temperature
- Base frame mounted fuel tank with minimum 8 hrs running capacity
- Dry type air filter with restriction indicator
- DG circuit breaker
- Electric start with battery
- Conveniently located fuel level indicator
- Exhaust tail pipe as standard scope of supply
- Weather proof enclosures to withstand harsh climate
- Ease of accessibility for all routine service points
- Riser blocks for lifting and handling

Conformance Standards

- ISO 9001-2015
- BS 5514
- ISO 14001

Generator Set Ratings

Genset	Engine	Alternator	Voltage	Phase	Hz	Prime Rating		Amps
						kWe	kVA	
GGP35EKL	G40-IV	Stamford/ Meccalte	415	3	50	28	35	49
GGP35EKL	G40-IV	Stamford/ Meccalte	230	1	50	28	35	152

PRIME POWER RATINGS: Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO-8528/1, overload power in accordance with ISO-3046/1 and BS 5514. For limited running time and base load ratings, consult the factory. Obtain the technical information bulletin (TIB-101) on ratings guidelines for the complete ratings definitions.

Engine Specifications

Specifications		35 KVA
Engine model		G40-IV
Engine aspiration		Turbo Charged
No. of cylinders & arrangement		3, Inline
Displacement, L (cc)		2760
Bore and stroke, mm		98x122
Compression ratio		17.5:1
Governor: type, Class		Electronic
Frequency regulation, steady state		IS 8528 P2
Air cleaner type, Qty		Dry, 1
Unit-mounted radiator ambient temperature °C (°F)		50 (122)
Max. power kWm (BHP) @ rated speed (rpm)		40.8 (57.6) @ 1500
Diesel Fuel Consumption		
100% Load (Lph)		7.32
75% Load (Lph)		5.94
Lube Oil Consumption		
100% load		0.1 % of SFC
Fuel System		
Fuel priming		Electronic
Fuel filter : Type, Qty		Combo fuel filter, 1
Recommended fuel		HSD-ASTM D2
Fuel tank capacity, L		130
Fuel filter change period		Initial - 100 hrs / 3 months, Subsequent 500 hrs / 12 months whichever is earlier
Lubrication System		
System type		Forced lubrication
Lube oil type		15W40
Oil pan capacity with filter, L		6.5
Oil filter: Quantity, Type		2, spin on & by-pass
Oil and oil filter change period		Initial - 100 hrs / 3 months, Subsequent 500 hrs / 12 months whichever is earlier
Exhaust System		
Max. allowable back pressure, KPa		9.2
Exhaust outlet size at engine hookup, mm (in)		50 (1.97)
Silencer Type, Quantity		Residential, 1
Exh. temperature at rated kW, dry exhaust, °C (°F)		550 (1022)
Cooling System		
Ambient temperature, °C (°F)		50 (122)
Coolant capacity including engine, L (gal)		12.5 (3.29)
Water pump type		Impeller
Fan diameter, including blades, mm (in.)		406.5 (16)
Engine Electrical System		
Starter Motor rated voltage VDC		12 V
Battery charging alternator		12 V , 35 Amp
Ground (negative/positive)		Negative
Battery type-		Lead acid
Amp/hour		100
Quantity		1
Battery voltage, VDC		12

Alternator Specifications

Specifications	35 KVA
Type	4 Pole
Exciter type	Brushless
Voltage regulator	AVR
Insulation	
- Material	Class H
- Temperature rise, Prime	125 °C
Bearing: Quantity, Type	1, Sealed
Coupling	Close coupled
Voltage regulation	+/-1%
Excitation	Self-excitation
Frequency, Fixed, Hz	50
Full load current - 3 phase	49
- 1 phase	152
Prime at 125 ° C, kVA	35

Advanced Digital Controller (ADC3003)

Standard Features

- Master switch: Control On/Off
- Event Log
- Remote two-wire start/stop capability
- One-source responsibility for generating system & accessories
- Automatic start with programmed cranking cycle
- Field software upgrade possibility
- Operating temperature: -20 °C to 70 °C (-4 °F to 158 °F)
- Storage temperature: -60 °C to 70 °C (-76 °F to 158 °F)
- Humidity: 0-95% condensing
- Control Panel
 - Alternator to control panel connection with copper cable only
 - MCCB/MCB details : with short circuit and overload protection
 - Inbuilt AMF controller



Up to 200 meter cable length	35 KVA
Output copper cable size (Sq. mm) : 3 Ph. (1 run)	12
Output copper cable size (Sq. mm) : 1 Ph. (1 run)	37

Optional Features

- Microprocessor based AMF change over panel
- Remote monitoring system

Controller Information

LCD Display	LCD Display Faults	Display Warnings	Optional Accessories	Power Requirements
Runtime hours	High engine temperature	Low battery voltage	Battery charger 12 V	8 to 35 V DC with fuse protection
Engine speed	Low oil pressure	High battery voltage	Earth leakage protection	85 mA @ 12 VDC
Power factor KVA	Over speed / under speed	Low fuel level	VAF meter (multifunction)	96 mA @ 24 VDC
Current	Over and under voltage	Maintenance alarm	kWh meter	
Voltage	Over and under frequency		Remote monitoring system	
Frequency	E-stop			
Engine temperature	Auxiliary fault			
Engine oil pressure	Low fuel level			
Battery voltage	Over load current			
Kilowatt & KVA	Phase reversal - for 3 phase			
Fuel level (in %age)				


Regulatory Compliance

Specifications	35 KVA
As per ISO 8178-5 mode cycle (Engine emission)	CPCB-IV compliant
Noise level measured at 1 meter distance	< 75 dB (A)

Dimensions and weight

Specifications	35 KVA
Overall Size, L x W x H (mm)	2250x1030x1470
Weight, dry, max (kg)	1000

NOTE : Drawing provided is for reference only and should not be used for planning installation. Please contact the Company for latest updated details.



* All the data is as per respective manufacturers' specification. Please refer O & M manual for maintenance and preservation guidelines.

* Fuel consumption data is based on HS Diesel having specific gravity of 0.85 and conforming to IS:1460 Standard. Fuel consumption tolerance is +5%.

GGP reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.

Corporate Office :

Gawade Green Power Solutions Pvt, Ltd.
Office. No. 210, 2nd floor, Laxmi Complex,
Near Big Bazar, old Pune Mumbai Highway,
Chinchwad Pune- 411019.
Maharashtra, India.

Authorized Channel Partner:

Factory :

Survey no 63/13, At Post AdarshGaon,
Gawadewadi Tal.Ambegaon, Dist.Pune.

ISO 9001:2015
ISO 14001:2015
GAWADE Green Power
IN POWER. SINCE 2014

Regional Offices :

Pune : +91 8956820181 | Mumbai : +91 8956820188
Nasik : +91 8956820183 | Nagpur : +91 8956820185
Amravati : +91 8956820186 | Kolhapur : +91 8956820182