

Ultrasonic Cleaner M Series

Key Industries

- Pharmaceuticals
- Hospital
- R & D Laboratories
- Jewellery
- PCB Cleaning



Technical Specification:

MODEL	M2	M3	M4.5	M5	M7	M10	M15	M22
Tank Size (mm) (L*W*H)	240* 140" *65	240x140x100	300x150x100	235x235x100	300x240x100	300x240x150	500x300x100	500x300x150
Outer Size (mm) (L*W*H)	265* 162*240	265* 162*240	325x176x240	265x265x250	320x276x210	325x276x260	525x320x345	530x320x400
Tank	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304
Enclosure	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304
Tank Capacity	2 Liter	3 Liter	4.5 Liter	5 Liter	7 Liter	10 Liter	15 Liter	22 Liter
Ultrasonic Power	50 Watts.	100 Watts.	100 Watts	100 Watts	200 Watts	250 Watts	300 Watts	400 Watts
Heater Power	100 Watts.	100 Watts.	100 Watts	200 Watts	200 Watts	200 Watts	500 Watts	500 Watts
PSP	NA	NA	Yes	Yes	Yes	Yes	Yes	Yes
Ultrasonic Freq. Khz.	33 ± 3	33 ± 3	33 ± 3	40/33 ± 3	40/33 ± 3	40/33 ± 3	40/33 ± 3	40/33 ± 3
Timer Digital	0 to 15 Min.	0 to 15 Min.	0 to 99 Min	0 to 99 Min	0 to 99 Min	0 to 99 Min	0 to 99 Min	0 to 99 Min
Power Input	230 VAC.	230 VAC	230 VAC	230 VAC	230 VAC	230 VAC	230 VAC	230 VAC
Degas Mode	On / Off	On / Off	On / Off	On / Off	On / Off	On / Off	On / Off	On / Off
Temperature	45°C (Inbuilt)	45°C (Inbuilt)	Amb. - 60 °c	Amb. - 60 °c	Amb. - 60 °c	Amb. - 60 °c	Amb. - 60 °c	Amb. - 60 °c
Transducer	Imported make PZT type bonded at the bottom of the tank with weld bond technique.							
Ultrasonic Gen.	Advance latest MOSFET / IGBT based smps.							
Accessories	Lid, Basket, Drain Valve, Powercord, User Friendly Operation Manual.							