

LP-46 Lite

Desktop BarCode Printer



FAST SPEED PRINTING



USER FRIENDLY DESIGN



POWER SAVING



CLEAR PRINTING QUALITY



LEGENDARY DURABILITY



Specification

Printing Method	: Thermal Line Printing - Direct Thermal & Thermal Transfer
Resolution	: 8 dots/mm (203 dpi)
Max. print speed	: 152.4 mm (6")/second
Max. print width	: 108 mm (4.25")
Max. print length	: 2,794 mm (110")
Enclosure	: ABS plastic
Physical dimension	: 204 mm (W) x 164 mm (H) x 280 mm (D) 8.03" (W) x 6.46" (H) x 11.02" (D)
Weight	: 2.4 kg
Label roll capacity	: 127 mm (5") OD
Ribbon	: 300 m long, max. OD 67 mm, 1" core (ink coated outside) 110 m long, max. OD 40 mm, 0.5" core (ink coated outside)
Ribbon width	: 40 mm ~ 110 mm (1.6" ~ 4.3")
Processor	: 32-bit RISC CPU
Memory	: 8 MB Flash memory ; 16 MB SDRAM
Interface	: USB 2.0
Power	: Input: AC 100-240V, 2.5A, 50-60Hz ; Output: DC 24V, 2.5A, 60W
Switch / Button	: 1 power switch, 1 feed and pause button & 1 LED
Sensors	: Transmissive gap sensor Black mark reflective sensor (position adjustable) Ribbon end sensor ; Head open sensor
Internal fonts	: 8 alpha-numeric bitmap fonts
Bar code	: 1D bar code, Code 128UCC, Code 128 subsets A, B, C, - EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code 39, Code 39 with check digit, Code 93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, etc.. 2D bar code, GS1 DataBar, GS1 DataMatrix, Maxicode etc.
Font/barcode rotation	: 0, 90, 180, 270 degree
Printer language	: TSPL-EZ (Compatible to EPL, ZPL, ZPL II, DPL)
Media type	: Continuous, die-cut, black mark, fan-fold, notched
Media width	: 20 ~ 112 mm (0.8" ~ 4.4")
Media thickness	: 0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
Media core diameter	: 25.4 ~ 38 mm (1" ~ 1.5")
Environment condition	: Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Warranty	: 1 Year Onsite

USER FRIENDLY DESIGN

- Superfast 6ips Speed
- Memory: 8 MB Flash, 16 MB SDRAM
- Interface: USB 2.0
- Print Head Life : 25 km



Segments



ORDERING INFORMATION

SKU No	SKU Title
3006210044	LP-46 LITE

© Copyright 2007. TVS Electronics Ltd. All rights reserved. All brand and product names are trademarks or registered trademarks of the respective holders and are hereby recognised as such. All product specifications are subject to change without prior notice.



TVS ELECTRONICS LIMITED

www.tvs-e.in

For Sales Enquiry

☎ 044 6688 8822
✉ sales-support@tvs-e.in

For Service Enquiry

☎ 1860 425 2078
✉ support@tvs-e.in