

LP-46 Plus

Desktop BarCode Printer

SUPERIOR, FAST, AFFORDABLE PERFORMANCE

USB, ETHERNET & SERIAL

FAST SPEED PRINTING

USER FRIENDLY DESIGN

POWER SAVING

CLEAR PRINTING QUALITY



Specification

Printing Method : Direct Thermal Transfer
 Resolution : 8 dots/mm (203 dpi)
 Max. print speed : 152.4 mm (6")/second
 Max. print width : 108 mm (4.25")
 Max. print length : 2,794 mm (110")
 Enclosure : ABS plastic
 Physical dimension : 204 mm (W) x 164 mm (H) x 280 mm (D)
 8.03" (W) x 6.46" (H) x 11.02" (D)
 Weight : 2.4 kg
 Label roll capacity : 127 mm (5") OD
 Ribbon : 300 m long, max. OD 67 mm, 1" core (ink coated outside)
 110 m long, max. OD 40 mm, 0.5" core (ink coated outside)
 Ribbon width : 40 mm ~ 110 mm (1.6" ~ 4.3")
 Processor : 32-bit RISC CPU
 Memory : 128 MB Flash memory ; 64 MB SDRAM
 Interface : USB 2.0, Ethernet & Serial Interface
 Power : Input: AC 100-240V, 2.5A, 50-60Hz ; Output: DC 24V, 2.5A, 60W
 Switch / Button : 1 power switch, 1 feed and pause button & 1 LED
 Sensors : Transmissive gap sensor
 Black mark reflective sensor (position adjustable)
 Ribbon end sensor ; Head open sensor
 Internal fonts : 8 alpha-numeric bitmap fonts
 Bar code : 1D bar code, Code 128UCC, Code 128 subsets A, B, C, -
 EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check
 digit, Code 39, Code 39 with check digit, Code 93, EAN13,
 EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, etc..
 2D bar code, GS1 DataBar, GS1 DataMatrix, Maxicode etc.
 Font/barcode rotation : 0, 90, 180, 270 degree
 Printer language : TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)
 Media type : Continuous, die-cut, black mark, fan-fold, notched
 Media width : 20 ~ 112 mm (0.8" ~ 4.4")
 Media thickness : 0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
 Media core diameter : 25.4 ~ 38 mm (1" ~ 1.5")
 Environment condition : Operation: 5 ~ 40°C, 25 ~ 85% non-condensing
 Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
 Dealer Option : Peel-off Module, • Guillotine cutter (full cut and partial cut)
 Warranty : 1 Year Onsite

USER FRIENDLY DESIGN

- Superfast 6ips Speed
- Memory: 128 MB Flash, 64 MB SDRAM
- Interface: USB 2.0, Ethernet & Serial Interface
- Print Head Life : 25 km



Segments



ORDERING INFORMATION

SKU No	SKU Title
3006210043	LP-46 PLUS