



**REACTIVE
VINYLE SULPHONE
DYES**

	Dischargeability	Suitability			Solubility		Fastness Properties				
		Hypochlorite Bleach	Reactivities	Printing Steam Silicate	With at 50° C Plain water	With at 50 g/l Salt	Light	Rubbing	Washing	Perspiration	
							0.25% 3.0%	Dry Wet	Shade Change Stain	Alkaline	Acidic
	Good	1	L	+	80	80	3-4 4	5 5	5 5	5	5
	Good	1	L	+	100	80	3-4 4	5 5	5 5	5	5
	Fair	1	H	+	100	80	4-5 5	4 4	5 4	5	5
	Good	1-2	H	+	100	90	4-5 5	5 4	5 4	5	5
	Good	1	H	+	80	60	5 6	5 4	5 4-5	4-5	4-5
	Good	1-2	H	+	80	60	4-5 5-6	4-5 5-6	4-5 3-4	5	5
	Good	1	H	+	100	80	5 6	5 4	5 4-5	4-5	4
	Good	1	L	(+)	120	110	4 5	5 4	5 5	5	5
	Good	1	H	(+)	80	60	4-5 6	5 4	5 5	5	5
	Good	1	M	+	120	100	4-5 5	5 4	5 4-5	5	5
	Good	1	VH	+	120	100	4 5	5 5	5 5	5	5
	Fair	1	H	(+)	100	80	6 7	5 5	5 5	5	5
	Good	2	H	+	120	100	5-6 7	5 5	5 4	5	5
	Fair	3	H	+	80	80	5 6	4 4	4-5 4	4-5	4-5
	Fair	3	H	+	80	80	5 6	4-5 4-5	5 4-5	4-5	4-5
	Good	3	H	+	80	60	6 7	5 4	5 4-5	4-5	4-5
	Good	2	VH	+	80	60	4 5	4 3-4	4 4-5	4	4

Fixation Temp. = 40 TO 60 °C, "L"= LOW, "M" = MEDIUM, "H"= HIGH, "VH"=VERY HIGH, TUR BLUE & TUR BLUE H2GP = Fixation Temp.= 80 to 85 °C