

MODEL NO.	BALANCING CAPACITY		TRAVEL in Mtr.	ROPE Dia Mm.	ROPE Dia Mm.
	Min. Kgs.	Max. Kgs.			
RTSB-1	0.25	1.5	1.5	2.0	1.0
RTSB-2	1.0	2.0	1.5	2.0	1.0
RTSB-3	1.0	3.0	1.5	2.5	1.8
RTSB-5	2.5	5.0	1.5	2.5	1.8
RTSB-9	4.5	9.0	1.5	4.0	4.2
RTSB-15	9.0	15.0	1.5	4.0	4.5
RTSB-22	15.0	22.0	1.5	5.0	9.0
RTSB-30	22.0	30.0	1.5	5.0	9.5
RTSB-40	30.0	40.0	1.5	5.0	10.5
RTSB-50	40.0	50.0	1.5	5.0	11.2
RTSB-60	50.0	60.0	1.5	5.0	12.6
RTSB-70	60.0	70.0	1.5	8.0	13.2
RTSB-85	70.0	85.0	1.5	8.0	25.0
RTSB-100	85.0	100.0	1.5	8.0	27.5
RTSB-120	100.0	120.0	1.5	8.0	30.5
RTSB-150	120.0	150.0	1.5	8.0	32.0
RTSB-180	150.0	180.0	1.5	8.0	35.0