

## AMRUT ENERGY PVT LTD

Voice- 9054333393 Mail- amrut@amrutenergy.com

## Solar LED Blinker



- High brightness LED operated solar traffic blinker
- No of LEDs: 180 LEDs, 12 inch diameter (300 mm)
- LED color: RED/AMBER
- > LED driver type: Micro-processer controlled dual PWM DC-DC buck driver
- ➢ Efficiency:
  - Minimum efficiency during full cycle: 90.62%
  - Maximum efficiency during full cycle: 94.80%
- Charge controller:
  - Optimized three stage battery charge monitoring algorithm
  - Battery low, load disconnect voltage: 10.70V
    - Battery full, charging cut-off : 13.80V
- Battery Anatomy: more than 48 hours(four night)
- > Protections:

0

- Short circuit protection
- Battery over charge protection
- Battery Deep discharge protection
- Solar panel reverse voltage polarity protection
- o Battery reverse voltage polarity protection
- Software watch-dog for LED over current protection
- Auto Dusk to Dawn functionality



Туре	No of LEDs	Solar panel	Battery	Pole height	Price
12 hour	180	15wp	12v, 7ah	12 feet	6800
24 hour	180	30wp	12v, 14ah	12 feet	8400

Note: Pole Excluding

## COMMERCIAL TERMS AND CONDITIONS

Transportation including at Your Nearest VRL Logistic Branch

Sales Tax : VAT 5% OR CST at actual

Delivery : Within 1 week from the date of receipt of confirmed order with advance.

Warranty : 24 months from the date of dispatch.