



An ISO 9001 : 2008 Certified Company

::: HIGH PRESSURE WASHING PUMP (DIESEL OPERATED):::



:: TECHNICAL DETAILS ::

Model	DHPW25	DHPW36A	DHPW36B
Pump Type	Radio-pump (Crankshaft)	Radio-pump (Crankshaft)	Radio-pump (Crankshaft)
Rated Pressure	170Bar (2500PSI)	250Bar (3600PSI)	250Bar (3600PSI)
Flow Rate	14L/min (3.7GPM)	15L/min (4GPM)	18L/min (4.7GPM)
Engine Type	D178F/E	D186F/E	D186FA/E
Engine Model	1-cylinder, vertical, 4-stroke, air-cooled	1-cylinder, vertical, 4-stroke, air-cooled	1-cylinder, vertical, 4-stroke, air-cooled
Displacement (cm ³)	296	406	418
Starting System	Recoil start; Electric start	Recoil start; Electric start	Recoil start; Electric start
Max. Output [KW(HP)/rpm]	4.0KW (5.5HP)/3600	6.3KW (8.6HP)/3600	6.3KW (8.6HP)/3600
Lube	SAE10W30 (above CC grade)	SAE10W30 (above CC grade)	SAE10W30 (above CC grade)
Fuel Type	0#(Summer), -10#(Winter) diesel oil	0#(Summer), -10#(Winter) diesel oil	0#(Summer), -10#(Winter) diesel oil