

# Sound Level Meter

## SL-1352

# HTC INSTRUMENTS

### Features :

MAX & MIN measurement

Over range display

Under range display

A & C Weighting

FAST & SLOW response

Analog AC/DC outputs for connection to frequency analyzer or X-Y shaft recorder

Datalogger function

Adjustable Alarm Levels

Backlight

**USB Computer Interface** (Advanced Software Program for all windows)



30~130 dB



PC interface



110V/220V AC  
adaptor



Backlight

### Technical Data :

Basic Functions	Range
Accuracy	$\pm 1.4$ dB
Resolution	0.1dB
Frequency Range	31.5Hz ~ 8KHz
Dynamic Range	50dB
Level Ranges	Low : 30dB ~ 80dB Medium : 50dB ~ 100dB High : 80dB ~ 130dB Auto : 30dB ~ 130dB
Time weighting	FAST (125ms), SLOW (1s)
Microphone	1/2 inch electret condenser microphone
Display Update	2 times/sec
Analog output	AC/DC outputs, AC = 1Vrms, DC = 10mV/dB



### Special Function :

Alarm	Electron	Power Supply	1 x 9VBattery
-------	----------	--------------	---------------

- **Standard Accessory** : Gift Box with Hard Carrying Casem, Manual, Battery, Screwdriver, Audio Plug, Windscreen, Tripod and DC 9V power supply, HTC USB with Software

- **Dimensions** : 278 x 76 x 50mm