



HDMP10-S0



SELECTION CHART


PUMP SPEED - 100 SPM (NOMINAL) GEAR RATIO 15:1 MOTOR 1500 RPM				MODEL	PL. Dia mm	Max. Pr. Kg/cm ²	PUMP SPEED - 185 SPM (NOMINAL) GEAR RATIO 8:1 MOTOR 1500 RPM			
Cap. LPH	Suc. Del. mmNB/BSP	% Of Max. Pr.	Motor k.w				Cap. LPH	Suc. Del. mmNB/BSP	% Of Max. Pr.	Motor k.w
1.5	15	ALL	0.37	HD MP 10-S 0	6	35	2.8	8	ALL	0.37
2.8	15				8	25	5	8		
4.2	15				10	20	7.8	8		
6.1	15				12	18	11.3	8		
11	15				16	15	20	15		
17	15				20	10	31	15		
24	15				24	7	45	15		

MOC CHART

Sr.No.	Description	MOC	Sr.No.	Description	MOC
1	Plunger	EN 8	1	NRV Sealing Ring	PTFE
2	Liquid Head	SS304, SS316, alloy20,P.P.,PVC,PTFE	2		
4	Non Return	SS304, SS316, alloy20,P.P.,PVC,PTFE	3	NRV Balls	SS, PTFE, Glass, Ceramic

FEATURES

- Multiple head pumps with common drive for mixing two or more liquid in a desired ratio.
The ratio can be easily reset.
- The design & Performance of MM Series Pumps conforms to API675.



DIMENSIONS IN MM

A	A1	B	C	D	E	F	
90	90	165	135	108	350	160	
G	H	I	J	K	L	M	N
320	Ø80	15	10	75	410	30	350

WEIGHT (App) : 28 KG.

PACKING SIZE : 18 x 16 x 16 Inches