Benchtop pH / mV / °C Meter APHS Series





AUTOMATIC CALIBRATION

The meters is capable of calibrating up to 3 points using USA or NIST pH standard buffer. Press CAL key to enter calibration mode and immerse pH electrode into indcated calibration solution, press ENTER key and meter is automatically calibrated.

AUTO-BUFFER RECOGNITION

During calibration, if the calibration solution does not match the meter's indicated value, and ERROR message is displayed.

VIEW ELECTRODE SLOPE

After calibration, the precentage slope of the electrode is displayed before the meter returns to measurement mode Per the stope value, you decides whether to change the pH electrode.

A U T O M A T I C T E M P E R A T U R E COMPENSATION (for PHS-3BW)

Using the suppled temperature probe, the temperature value is displayed on the screen. The meters provides manual or automatic temperature compensation mode for optimum accuracy under variable temperature conditions.

FLUID RESISTANT HOUSING AND SWIVEL ELECTRODE HOLDER

The integrated plastic housing and keypad is sealed to protect against accidental spills and splashes. The electrode holder arm is rapidly switched to both sides and swivels and articulates for convenient use and positioning.

METER INCLUDES

pH Electrode, pH Buffers. Temperature Probe (for APHS-3BW). Electrode Holder, 9V Power Adapter

| Model | APHS-25CW | APHS-3CW | APHS-3BW |
|--------------------|--|-----------------|------------------------------|
| pH Range | 0.00~14.00pH | 0.00~14.00pH | 0.00~14.00pH |
| pH Accuracy | ±0.05pH | ±0.01pH | ±0.01pH |
| mV Range | 0~ ±1999mV | 0~ ±1999mV | 0~ ±1999mV |
| mV Accuracy | ±10mV | ±1mV | ±1mV |
| Temp. Range | | | 0~100°C |
| Temp. Accuracy | | | ±1°C |
| Calibration Points | 2 points | | |
| pH Buffer options | NIST (pH 4.00/6.86/9.18), USA (pH 4.01/7.00/10.00) | | |
| Temp. Compensation | 0~100°C, Manual | 0~100°C, Manual | 0~100°C, Automatic or Manual |
| Power Requirements | DC9V, using AC adapters, 220VAC/50Hz | | |
| Dimensions | 210 (L) x 205 (W) x 65 (H)mm | | |
| Weight | 1.7kg | | |

Specification are subject to change without prior notice. Images shown are for illustrations purpose only.

WORLD WIDE MARKETING

ACZET PVT. LTD.

Unit E2, Plot No. 15, WICEL Estate, Opp Seepz Gate Nol. 1, Andheri (E), Mumbai 400 093. (INDIA) Tel. : +91-22-4243 7700 • Fax : +91-22-4243 7800 • E-mail : sales@aczet.com • Web : www.aczet.com