

Head Office:

MARS Complex, Poothole Road, Thrissur, Kerala India - 680 004. Ph: +91 487-2385001, 2385002 E-mail: customerservice@starline.in www.starlineenterprises.in

Factory:

Sree Sai Krithika Industrial Estate 4 / 293, S.F. No. 221 & 91, Sreerapalayam, Post - Podipalayam, Coimbatore, Tamil Nadu, India - 641 105

Open Spring Mounts - Rubber Based 25 mm Standard Deflection

Catalogue Number : 9000110 : Rev. 01 Dated 07-10-2014

1. Compliance:

- a) Designed to BS 1726 -1: 1987
- b) Tolerance to BS 1726-1 : 2002
- c) SAE and Ashrae Guidelines for Vibration Isolation

2. Application:

a) Centrifugal axial fans, Air Handling Units, small compressors.

3. Product Features:

- a) Laterally Stable Springs are designed to prevent Spring Buckling and capable of 50% overloading capacity.
- b) Springs are powder coated with 100 hours Salt Spray Testing conforming to ASTM B-117.
- c) In heavier capacities, Springs are welded to Load Plate.
- d) Bottom Plates are made of thick ribbed Neoprene Pad for isolation of noise / vibration and non skid base.
- e) Standard Product Range upto 2" deflection and Custom Isolators with higher deflections are available.
- f) Upper Load Plate and Levelling Assembly are provided for accurate Leveling.
- g) Colour Coded Springs are provided for easy identification.

4. Selection / Ordering:

a) Static Load

5. Installation Guide lines:

a) Included in packing.



Isolator Model	Rated Load (kg)	Colour Code	Dimensions (mm)					
			L	W	H*	BC	D	d
SOSM-A25	25	Green	86	56	110	73	M10	M8
SOSM-A50	50	Black						
SOSM-A75	75	Yellow						
SOSM-A100	100	Blue	86	56	118	73	M10	M8
SOSM-A150	150	Grey						
SOSM-A200	200	Orange						
SOSM-B200	200	Black	- 100	65	124	85	M10	M10
SOSM-B250	250	Yellow						
SOSM-B300	300	Blue						
SOSM-B400	400	Grey						
SOSM-C400	400	Brown	130	76	132	110	M12	M12
SOSM-C500	500	Grey						
SOSM-C600	600	Orange						
SOSM-C700	700	Green	130	76	138	110	M12	M12
SOSM-C800	800	Pink						
SOSM-C1000	1000	White						
SOSM-C1200	1200	Purple						
SOSM-C1400	1400	Purple/Yellow						
SOSM-C1600	1600	Purple/White						

Selection Table for 25 mm Deflection Open Spring Mounts (Table No: C-24-01)

* Represents average free height in each grouping of Models. Height of some models in group may vary slightly from this figure.



