

(ERP) ESWAR RUBBER PRODUCTS PVT LTD.,

AN ISO 9001: 2015 CERTIFIED COMPANY

Admin Office: Surya Towers, 12, Maravaneri Extension 2nd Cross, Salem – 636007, India. Contact: Ph:+91-427-4047677, 2452271. Email:info@rubberreclaim.com. Web:www.rubberreclaim.com

Rev.No:01 / 05.01.2017

PRODUCT DATA SHEET

Product Name **Butyl Reclaim Rubber**

Grade ERP-501

Black slab rubber Sheets Appearance

STANDARD SPECIFICATION

S.NO	PROPERTIES	UNITS	LIMITS	TEST METHOD
CHEMICAL PROPERTIES				
1	ACETONE EXTRACT	%	10+/-3	IS 6306-1971
2	ASH CONTENT	%	4+/-2	IS 6306-1971
3	CARBON BLACK	%	Min 28	IS 6306-1971
4	RUBBER HYDROCARBON	%	Min 50	IS 6306-1971
5	VOLATILE MATTER	%	Max 1	IS 6306-1971
PHYSICAL PROPERTIES				
6	SPECIFIC GRAVITY		1.12+/-0.02	IS 6306-1971
7	TENSILE STRENGTH	KG/SQ.CM	Min 80	IS 3400-1987
8	ELONGATION AT BREAK	%	Min 480	IS 3400-1987
9	HARDNESS	SHORE 'A'	55+/-5	IS 3400-1980
10	MOONEY VISCOSITY ML (1+4) @ 100°C	MU	3045	IS 6306-1971

Test Recipe: (Parts by Mass): Reclaim – 200, Zinc Oxide -5.0, Sulphur-2.0,

MBTS-0.5, TMTD-1.0, Cure : slab - 160°C / 30 min

REACH (EU) Compliance: Our products are registered under REACH EU Regulation (EC) No:1907/2006 (REACH)

Very fine Grade Reclaimed Rubber produced out of Butyl Scrap inner tubes by the application of Description:

heat and chemical agents, followed by intense mechanical process.

Packing Option: HDPE Sacks - 25Kgs & 50Kgs, LDPE Bag - 25Kgs, EVA packing - 20Kgs & 10Kgs,

Pallet packing - 1MT.

Detailed advice on the Health safety aspects of this product is given in the individual product Health & Safety:

Material safety Datasheet (MSDS), available upon request.



