



MODEL : CXW

Available in Size : 50mm(2") To 300mm (12")

Features :

- Water Meter Conforming to International Standard ISO : 4064 Class - B and IS : 2373/81.
- Horizontal Flow, Woltman Type, Magnetically Driven
- Suitable for :
 High Rise Buildings, Industrial Use, Irrigation and main Distribution Pipe Lines.
 Cold Water Temp. Upto 45° C
 Hot Water Temp. Upto 80° C

Technical Specifications :

Size	Permissible error	DN50 (2")	DN65 (2½")	DN80 (3")	DN100 (4")	DN150 (6")	DN200 (8")	DN250 (10")	DN300 (12")
Maximum Flow Rate	(± 2%) kl/h	30	50	80	120	300	500	800	1200
Nominal Flow Rate	(± 2%) kl/h	15	25	40	60	150	250	400	600
Transitional Flow Rate	(± 2%) kl/h	3	5	8	12	30	50	80	120
Minimum Flow Rate	(± 5%) kl/h	0.45	0.75	1.2	1.8	4.5	7.5	12	18
Max. Working Pressure	bar	16	16	16	16	16	16	16	16

Dimensions :

Size	»	DN 50	DN65	DN 80	DN 100	DN 150	DN 200	DN 250	DN 300	
Connecting Pipe Size	»	2"	2½"	3"	4"	6"	8"	10"	12"	
Length Face to Face (mm)	»	200	200	220	250	300	350	450	500	
Height (mm)	»	270	275	285	290	320	370	480	550	
Outside Diameter of Flange (D)	»	165	185	200	220	285	340	395	445	
Bolt Circle Diameter	»	125	145	160	180	240	295	350	400	
Holes	Number	»	4	4	4	8	8	8	12	12
	Diameter	»	17	17	21	22	23	23	23	23



**VISHWAKARMA
WATER METER
SALES & SERVICE**
18- SURYA SOCIETY,
LAXMIPURA ROAD
GORWA VADODARA
390016
(M) 09924118230