

### 3. LDX1920.1080\_520\_400\_B600

#### Specification

LDX1920.1080\_520\_400\_B600

Model No.	LDX1920.1080_520_400_B600
Resolution	1920*1080
Active Image area	1155*652 (mm)
Outline dimensions	Customize
Brightness	0.5nit-600nits
Contrast ratio(dark ambient)	>300:1@ 0H/0V
Brightness non-uniformity	≤20%
Viewing envelope (CR >5:1)	±80° (H), ±80° (V)
Video Signal input	DVI or VGA
Gray shades (colors)	256 level
Extensive Built-In Testing (BIT)	RS232/422
Power supply	220 VAC
Power consumption	Normal temperature power consumption≤400W
Weight	≤75kg
Environment suitability	
Work temperature	-15degree ~60degree

Storage temperature	-45degree~70degree
Humidity	95%@ 60degree
Vibration	To staify be corresponding standard
EMC	To staify be corresponding standard
MTBF(MIL-STD-217)	10000 hours

## Product model explanation

LDX1920.1080\_520\_400\_B600:

LDX—LCD display

1920.1080—Resolution is 1920x1080

520—Dimension of the LCD panel is 52 inch.

400—Power consumption is not more than 400W under normal temperature.

B600—Max Brightness is more than 600 cd/m<sup>2</sup>.

Supplied by: Gus Industry (Hongkong)Co.,Limited